

Suspended lamp for indirect lighting with integrated LED source and diffused light optic system.


Aluminium structure with steel matt-painted reflector.


1-10V dimming or DALI dimming available.

The decentralizing kit is always included.

Finishing

Standard

 Anodised black
cod. 131D01XO00

 Anodised brass
cod. 131D50XO00

All RAL coating and galvanic finishes available upon request

Light emission

- Light emission: diffuse
- Light direction: indirect downlight
- Light source: led board
- Source flux: 3250 lm
- Emitted flux: 1780 lm
- Efficacy: 43 lm/W
- CCT: 3000K
- CRI index: 83
- Lifetime: >50000h L70 @ 25°C

Electrical Facts

- Source power: 39 W
- Power absorption: 41 W
- Stand-by absorption: < 2 W
- Grid voltage: 100-240V AC/50-60 Hz
- Power supply: internal AC-DC converter provided
- Dimmability: 1-10V, DALI dimmable
- Energy class: A++

Technical data

- Environment: indoor
- Placement: pendant
- Net weight: 7,7 Kg
- Certifications: CE
- Suggested ambient T: 25°C
- Maximum ambient T: 40°C
- Insulation class: I
- Protection class: IP20

Packaging
cardboard box
90 x 90 x 28 (cm)
0,30 m³

Gross weight
18 Kg

